







Compact and affordable



-
-
-
-
-

Innovative multifunctionality




SAVE SPACE



OPTIMISE YOUR PRODUCTIVITY




IMPROVE YOUR WORKFLOW




SIMPLE TO OPERATE



EASY NETWORKING



HIGHLY SECURE



WIDE MEDIA VERSATILITY



ENVIRONMENTALLY FRIENDLY



COPIER

Copying process:	Single laser beam scanning & electro-photographic printing
Copy speed:	23/28/28/33/33 copies per minute
Resolution:	600 dpi
Warm-up time:	Less than 20 seconds
First output speed:	5.4/4.5/4.5/4.5/4.5 seconds
Memory:	Maximum: 1 GB + 120 GB HDD
Paper input capacity:	Maximum: 3,150 sheets
Paper output capacity:	Maximum: 1,625 sheets
Paper size:	A6 - A3
Paper weight:	Paper tray: 52 - 157 g/m ² Bypass tray: 52 - 157 g/m ² Duplex tray: 52 - 105 g/m ²
Dimensions (W x D x H):	587 x 653 x 829 mm (with ARDF)
Weight:	Less than 65 kg (less than 75 kg with ARDF)
Power source:	220 - 240 V, 50/60 Hz
Power consumption:	Maximum: Less than 1.6 kW

PRINTER

Print speed:	23/28/28/33/33 prints per minute
Printer language:	Standard: PCL5e, PCL6, Adobe PDF Direct, Option: Adobe® PostScript® 3™, IPDS Maximum 600 x 600 dpi
Resolution:	Maximum 600 x 600 dpi
Interface:	Standard: USB 2.0, Ethernet 10 base-T/100 base-TX, Option: IEEE 1284/ECP, Wireless LAN (IEEE 802.11a/b/g), Bluetooth, Gigabit Ethernet
Network protocol:	TCP/IP (IPv4, IPv6), IPX/SPX
Supported environments:	Windows® XP/Vista/7/Server 2003/Server 2008, Novell® NetWare® 6.5 or later, UNIX Sun® Solaris 2.6/7/8/9/10, HP-UX 10.x/11.x/11iv2/11iv3, SCO OpenServer 5.0.6/5.0.7/6.0, RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise, IBM® AIX v4.3/5L v5.1/5.2/5.3, Macintosh X v10.2 or later, NDPS Gateway Netware 6.5 (SP3 or later), IBM iSeries/AS400 using OS/400 Host Print Transform, Citrix Presentation Server 4.5/Citrix XenApp 5.0

SCANNER

Scan speed:	Full colour: Maximum 45 ipm B/W: Maximum 50 ipm
Resolution:	Maximum 600 dpi
Original size:	A5 - A3
Bundled drivers:	Network TWAIN
Scan to e-mail:	SMTP, TCP/IP
Scan to folder:	SMB, FTP, NCP protocol (with login security)

SOFTWARE SOLUTIONS

SmartDeviceMonitor™, Web SmartDeviceMonitor™, Web Image Monitor

FAX (OPTION)




Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3, ITU-T (T.37) Internet Fax, ITU-T (T.38) IP Fax Maximum: 33.6 Kbps
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	0.5 seconds (A4/SEF/standard mode)
Memory capacity:	4 MB standard, 36 MB max.
Memory backup:	Yes

OTHER OPTIONS

50-sheet ARDF¹, Platen cover¹, 1 x 550-sheet paper tray, 2 x 550-sheet paper trays, 2,000-sheet LCT, One-bin tray, Internal shift tray, 500-sheet internal finisher, 500-sheet external finisher, 1,000-sheet finisher, 1,000-sheet booklet finisher, Punch kits, Bridge unit, Hard Disk Drive option¹, Memory unit¹, Printer/scanner unit¹, Printer unit¹, Scanner enhance option¹, PostScript 3 unit, IPDS unit, VM card¹, USB2.0/SD slot, Fax option, G3 interface unit, Memory unit for fax, Bluetooth interface, IEEE 802.11 a/g interface, Gigabit Ethernet board, IEEE 1284 interface board, Unicode font package, File format converter, Browser unit, Caster table, Card reader bracket, Accessibility handle, Counter interface unit, Key counter bracket, Professional software solutions

¹ MP 2852/MP 3352 only.

For availability of models, options and software, please consult your local Ricoh supplier.



RICOH

www.ricoh-europe.com

For more information, please
contact